



SMD technology, for a high quality of light and a very good longevity



Easy to install



Waterproof (IP67) and corrosion resistant.



Adjustable brightness switch (depending on model)



Operating temperature range : -20°C / +80°C



Certification E-mark - R10
Conformité CEM automobile



Quality guaranteed by Uniteck,
Made in P.R.C.

Led ceiling lights UNILEDLIGHT

ROBUSTNESS AND POWER

UNILEDBAR is the last generation high performance 12/24V spotlight led range.

Made with the best led-technology of the market in reference to their lighting quality and their lifespan (CREE Led - USA).

UNILEDBAR generates a consistent luminous beam similar to the natural brightness.

The visual field is completely enlightened, which offers perfect visibility while avoiding ocular fatigue.

Waterproof (IP67) and corrosion-resistant (aluminium structure, inox mounting brackets, ...), UNILEDBAR is made for all outdoor uses even the most challenging (boating, campervan, truck, ...).





**UNILEDLIGHT
18.24 R**

Ref 3331



**UNILEDLIGHT
18.24 RB**

Ref 3348



**UNILEDLIGHT
12.24 L**

Ref 3355



**UNILEDLIGHT
12.24 LB**

Ref 3362



**UNILEDLIGHT
26.24 L**

Ref 3379



**UNILEDLIGHT
26.24 LB**

Ref 3386

System

Technology	LED	LED	LED	LED	LED	LED
Operating voltage	10-30V DC	10-30V DC	10-30V DC	10-30V DC	10-30V DC	10-30V DC
Maximum power	18W	18W	12W	12W	26W	26W
Actual consumption	9W	9W	10W	10W	15W	15W

Battery

Accepted battery voltage	12 or 24V	12 or 24V	12 or 24V	12 or 24V	12 or 24V	12 or 24V
--------------------------	-----------	-----------	-----------	-----------	-----------	-----------

Lighting

Number of leds	91 x 0,2W	91 x 0,2W	58 x 0.2W	58 x 0,2W	134x0.2W	134x0.2W
Lumens	650lm	650lm	400lm	400lm	600lm	600lm
Adjustable brightness	no	yes	no	yes	no	yes

Beam

Bright color	Cold white 5800-6250K	Cold white 5800-6250K	Neutral white 3800-4250K	Neutral white 3800-4250K	Neutral white 3800-4250K	Neutral white 3800-4250K
Lifetime	>50 000 hours	>50 000 hours	>50 000 hours	>50 000 hours	>50 000 hours	>50 000 hours

Mechanical characteristics

Materials						
Lenses	Polycarbonate	Polycarbonate	Polycarbonate	Polycarbonate	Polycarbonate	Polycarbonate
Body - Dissipators	ABS	ABS	ABS + Aluminium	ABS + Aluminium	ABS + Aluminium	ABS + Aluminium
Integrated switch	no, remote connection	yes, tactile	no, remote connection	yes, tactile	no, remote connection	yes, tactile

Cable

Length	22cm	22cm	22cm	22cm	22cm	22cm
Type	simple strand	simple strand	simple strand	simple strand	simple strand	simple strand
Section	2 x 0,33mm ²	2 x 0,33mm ²	2 x 0,33mm ²	2 x 0,33mm ²	2 x 0,33mm ²	2 x 0,33mm ²
Operating temperature	-20°C/+80 °C	-20°C/+80 °C	-20°C/+80 °C	-20°C/+80 °C	-20°C/+80 °C	-20°C/+80 °C
Protection class	IP67	IP67	IP67	IP67	IP67	IP67

Dimensions (L x W x H) in mm	Ø 130x12	Ø 130x12	300x54x12	300x54x12	600x54x12	600x54x12
---------------------------------	----------	----------	-----------	-----------	-----------	-----------

Weight	140 g	140 g	275 g	275 g	550 g	550 g
--------	-------	-------	-------	-------	-------	-------

Warranty

Period	2 years	2 years	2 years	2 years	2 years	2 years
--------	---------	---------	---------	---------	---------	---------